



**GLORY**

# PRODUCT CATALOGUE

**Agricultural machinery-Tractor**



**Qingdao Ever Glory Machinery Co., Ltd**

[www.everglorymachinery.com](http://www.everglorymachinery.com)  
Email: [market@everglorymachinery.com](mailto:market@everglorymachinery.com)

TEL : +86-18153282521



# GLORY

## About GLORY

---



GLORY Machinery Group, located in Qingdao, specializes in the design, develop and production of construction and agricultural machinery. The products covers mining machinery, road machinery, agricultural machinery and so on.

With nearly 20 years of industry experience, GLORY machinery has been exported to South America, Europe, the Middle East, Southeast Asia, Africa and other more than 30 countries and regions.

GLORY has modern production workshops, advanced production lines, multi-functional laser cutting equipment, CNC bending machine, welding machine and other intelligent production equipments. GLORY has researched and manufactured more than 100 models of machinery, which also independently researches the axle by ourselves. GLORY could supply a variety of construction and agricultural implements to achieve one stop solutions, which could meet many conditions and improve the work efficiency.

In order to provide customers with immersive experience services, GLORY has branches in Singapore and Philippines to ensure timely and effective supports for our customers.

GLORY is committed to building the long-term and stable cooperation with customers and achieving the common development.



# GLORY

## About GLORY

---



### Experience

20+  
industry  
experience

Patents  
Research and  
develop  
independently

### Branches

The direct  
branches for  
support

Cooperate  
Cooperate  
with  
customer  
always



# GLORY



## Classis

Assembling independently ensures the stable quality



## Axle

Research, develop and assemble independently



## Engine

Laidong KM495, Huafeng 4102 are available.



## Cab

Electrophoretic paint which is more rust-proof





# GLORY

Various of agricultural implements for option, such as Plow, Harrow, Rotary tiller, Seeder, Fertilizer spreader, Mower, etc.



Moldboard plow



Turnover plow



Disc plow



Disc harrow



Powered harrow



Rotary harrow



Rotary tiller



Seeder



Seeder



Fertilizer spreader



Mower



Cultivator



Subsoiler



Deep loosening cultivator



# GLORY

## Tractor **GL254**

Min operating weight  
**1700KG**

Rated power (KW)  
**18.4kw**

Rated speed(r/min)  
**2400r/min**



## GL254 technical specifications

### GL254-TY

Model	GL254
Dimensions with frame (mm)	3640*1530*2330
Dimensions with cab (mm)	3640*1530*2530
Wheelbase (mm)	1860
Min operating weight (kg)	1550(Without cab)/1700(With cab)
Min ground clearance (mm)	330
Emission standard	National II
Engine standard	LaiDong KM385Z
Optional engines	/
Pattern	Inline 4 cylinder
Rated power (KW)	18.4
Rated speed (r/min)	2400
Clutch	10inch ; Dry ; Single disc
Gearbox	8+2(Optional8+8)
Axle	TY
Tire	6.00-16/9.5-24
PTO speed (r/min)	540/720
Hydraulic lifting system type	Strong pressure double cylinder
Balance weight	Front11KG×4/Rear25KG×2



# GLORY



## Tractor **GL504**

Min operating weight  
**1900KG**

Rated power (KW)  
**36.8kw**

Rated speed(r/min)  
**2400r/min**

## GL504 technical specifications

GL504-TE	
Model	GL504
Dimensions with frame (mm)	3740×1530×2330
Dimensions with cab (mm)	3740×1530×2530
Wheelbase (mm)	1870
Min operating weight (kg)	1750(Without cab)/1900(With cab)
Min ground clearance (mm)	350
Emission standard	National II
Engine standard	LaiDong KM495Z
Optional engines	Laidong 490T, Yunnei YN25Z, Yangdong 490Z, Changchai 490Z, Sida 490Z
Pattern	Inline 4 cylinder
Rated power (KW)	36.8
Rated speed (r/min)	2400
Clutch	10inch ; Dry ; Single disc
Gearbox	8+8(Optional8+2)
Axle	TE
Tire	7.50-16/11.2-28
PTO speed (r/min)	540/720
Hydraulic lifting system type	Strong pressure double cylinder
Balance weight	Front11KG×4/Rear25KG×2



# GLORY

## Tractor **GL704**

Min operating weight  
**2580KG**

Rated power (KW)  
**51.5kw**

Rated speed(r/min)  
**2400r/min**



## GL704 technical specifications

### GL704-TBS

Model	GL704
Dimensions with frame (mm)	4030×1750×2500
Dimensions with cab (mm)	4030×1750×2700
Wheelbase (mm)	2050
Min operating weight (kg)	2380(Without cab)/2580(With cab)
Min ground clearance (mm)	380
Emission standard	National II
Engine standard	LaiDong KM4102Z
Optional engines	YTO 4108Z,Yunnei YN38T,Yangdong 4100T,Changchai 495T,Sida 4102Z
Pattern	Inline 4 cylinder
Rated power (KW)	51.5
Rated speed (r/min)	2400
Clutch	10inch ; Dry ; Double disc
Gearbox	12+12(Optional16+8)
Axle	TBS
Tire	8.3-24/11-32
PTO speed (r/min)	540/760
Hydraulic lifting system type	Strong pressure double cylinder
Balance weight	Front25KG×6/Rear25KG×2





# GLORY



Tractor  
**GL904**

Min operating weight  
**2780KG**

Rated power (KW)  
**66.2kw**

Rated speed(r/min)  
**2400r/min**

## GL904 technical specifications

GL904-TBL	
Model	GL904
Dimensions with frame (mm)	4030×1750×2500
Dimensions with cab (mm)	4030×1750×2700
Wheelbase (mm)	2050
Min operating weight (kg)	2580(Without cab)/2780(With cab)
Min ground clearance (mm)	380
Emission standard	National II
Engine standard	LaiDong KM4102ZT
Optional engines	Laidong 4108T, Yunnei YN38T, Yangdong 4105T, Changchai 4102T, Sida 4105T
Pattern	Inline 4 cylinder
Rated power (KW)	66.2
Rated speed (r/min)	2400
Clutch	11inch ; Dry ; Double disc
Gearbox	12+12(Optional16+8)
Axle	TBL
Tire	9.5-24/14.9-30
PTO speed (r/min)	540/760
Hydraulic lifting system type	Strong pressure double cylinder
Balance weight	Front25KG×8/Rear45KG×4



# GLORY

## Tractor **GL1004**

Min operating weight  
**4100KG**

Rated power (KW)  
**73.5kw**

Rated speed(r/min)  
**2200r/min**



## GL1004 technical specifications

### GL1004-TD3S

GL1004-TD3S	
Model	GL1004
Dimensions with frame (mm)	4920×2210×2830
Dimensions with cab (mm)	4920×2210×3030
Wheelbase (mm)	2550
Min operating weight (kg)	3800(Without cab)/4100(With cab)
Min ground clearance (mm)	380
Emission standard	National II
Engine standard	Weichai Huafeng4105T
Optional engines	YTO 4110T
Pattern	Inline 4 cylinder
Rated power (KW)	73.5
Rated speed (r/min)	2200
Clutch	12inch ; Dry ; Double disc
Gearbox	12+12
Axle	TD3S
Tire	12.4-24/16.9-34
PTO speed (r/min)	760/850
Hydraulic lifting system type	Strong pressure double cylinder
Balance weight	Front40KG×11/Rear43KG×4



# GLORY

## Tractor **GL1204**

Min operating weight  
**4300KG**

Rated power (KW)  
**88.2kw**

Rated speed(r/min)  
**2200r/min**



## GL1204 technical specifications

### GL1204-TD

GL1204-TD	
Model	GL1204
Dimensions with frame (mm)	4920×2210×2830
Dimensions with cab (mm)	4920×2210×3030
Wheelbase (mm)	2550
Min operating weight (kg)	4000(Without cab)/4300(With cab)
Min ground clearance (mm)	490
Emission standard	National II
Engine standard	Weichai Huafeng4105T (Lovol style)
Optional engines	YTO 4110T
Pattern	Inline 4 cylinder
Rated power (KW)	88.2
Rated speed (r/min)	2200
Clutch	14inch ; Dry ; Double disc
Gearbox	16+8/(Optional12+12)
Axle	TD
Tire	12.4-24/16.9-34
PTO speed (r/min)	760/850
Hydraulic lifting system type	Strong pressure double cylinder
Balance weight	Front40KG×11/Rear43KG×4



# GLORY

## Tractor **GL1304**

Min operating weight  
**4400KG**

Rated power (KW)  
**95.6kw**

Rated speed(r/min)  
**2200r/min**



## GL1304 technical specifications

### GL1304-TD

GL1304-TD	
Model	GL1304
Dimensions with frame (mm)	4920×2210×2830
Dimensions with cab (mm)	4920×2210×3030
Wheelbase (mm)	2550
Min operating weight (kg)	4100(Without cab)/4400(With cab)
Min ground clearance (mm)	490
Emission standard	National II
Engine standard	Weichai Huafeng4105T (Lovol style)
Optional engines	Weichai Huafeng 6105Z,YTO 4110T
Pattern	Inline 4 cylinder
Rated power (KW)	95.6
Rated speed (r/min)	2200
Clutch	14inch ; Dry ; Double disc
Gearbox	16+8/(Optional24+8)
Axle	TD
Tire	12.4-24/16.9-34
PTO speed (r/min)	760/850
Hydraulic lifting system type	Strong pressure double cylinder
Balance weight	Front40KG×11/Rear43KG×4



# GLORY

## Tractor **GL1604**

Min operating weight  
**5780KG**

Rated power (KW)  
**117.6kw**

Rated speed(r/min)  
**2200r/min**



## GL1604 technical specifications

### GL1604-TF

GL1604-TF	
Model	GL1604
Dimensions with frame (mm)	5050×2400×2800
Dimensions with cab (mm)	5050×2400×3000
Wheelbase (mm)	2630
Min operating weight (kg)	5480(Without cab)/5780(With cab)
Min ground clearance (mm)	470
Emission standard	National II
Engine standard	YTO 6M
Optional engines	Weichai Huafeng 6118Z
Pattern	Inline 4 cylinder
Rated power (KW)	117.6
Rated speed (r/min)	2200
Clutch	14inch ; Dry ; Double disc
Gearbox	16+8/(Optional24+8)
Axle	TF
Tire	14.9-26/18.4-38
PTO speed (r/min)	760/850 760/1000
Hydraulic lifting system type	Strong pressure double cylinder
Balance weight	Front40KG×11/Rear60KG×4



# GLORY

## Tractor **GL1804**

Min operating weight  
**5980KG**

Rated power (KW)  
**132.4kw**

Rated speed(r/min)  
**2200r/min**



## GL1804 technical specifications

GL1804-TF	
Model	GL1804
Dimensions with frame (mm)	5050×2400×2800
Dimensions with cab (mm)	5050×2400×3000
Wheelbase (mm)	2630
Min operating weight (kg)	5680(Without cab)/5980(With cab)
Min ground clearance (mm)	470
Emission standard	National II
Engine standard	YTO 6M
Optional engines	Weichai Huafeng 6118Z
Pattern	Inline 4 cylinder
Rated power (KW)	132.4
Rated speed (r/min)	2200
Clutch	14inch ; Dry ; Double disc
Gearbox	16+8/(Optional24+8)
Axle	TF
Tire	14.9-26/18.4-38
PTO speed (r/min)	760/850 760/1000
Hydraulic lifting system type	Strong pressure double cylinder
Balance weight	Front40KG×11/Rear60KG×4



# GLORY

## Tractor **GL2004**

Min operating weight  
**6450KG**

Rated power (KW)  
**147.0kw**

Rated speed(r/min)  
**2200r/min**

## GL2004 technical specifications

### GL2004-TF

Model	GL2004
Dimensions with frame (mm)	5050×2400×2800
Dimensions with cab (mm)	5050×2400×3000
Wheelbase (mm)	2630
Min operating weight (kg)	6150(Without cab)/6450(With cab)
Min ground clearance (mm)	470
Emission standard	National II
Engine standard	YTO 6M
Optional engines	Weichai Huafeng 6118Z
Pattern	Inline 4 cylinder
Rated power (KW)	147.0
Rated speed (r/min)	2200
Clutch	14inch ; Dry ; Double disc
Gearbox	16+8/(Optional24+8)
Axle	TF
Tire	14.9-26/18.4-38
PTO speed (r/min)	760/850 760/1000
Hydraulic lifting system type	Strong pressure double cylinder
Balance weight	Front40KG×11/Rear60KG×4



# GLORY



## Tractor **GL2404**

Min operating weight  
**7800KG**

Rated power (KW)  
**177.0kw**

Rated speed(r/min)  
**2200r/min**

## GL2404 technical specifications

### GL2404-TS

Model	GL2404
Dimensions with frame (mm)	5600×2780×3000
Dimensions with cab (mm)	5600×2780×3200
Wheelbase (mm)	2830
Min operating weight (kg)	7400(Without cab)/7800(With cab)
Min ground clearance (mm)	450
Emission standard	National II
Engine standard	Yuchai
Optional engines	Shangchai
Pattern	6 cylinder
Rated power (KW)	177.0
Rated speed (r/min)	2200
Clutch	15inch ; Dry ; Double disc
Gearbox	16+16/(Optional32+32)
Axle	TS
Tire	16.9-28/18.4-42
PTO speed (r/min)	760/850 850/1000
Hydraulic lifting system type	Strong pressure double cylinder
Balance weight	Front40KG×11/Rear60KG×4





# GLORY

## Tractor **GL2604**

Min operating weight

**8500KG**

Rated power (KW)

**191.2kw**

Rated speed(r/min)

**2200r/min**

## GL2604 technical specifications

### GL2604-TS

GL2604-TS	
Model	GL2604
Dimensions with frame (mm)	5600×2780×3000
Dimensions with cab (mm)	5600×2780×3200
Wheelbase (mm)	2830
Min operating weight (kg)	8100(Without cab)/8500(With cab)
Min ground clearance (mm)	450
Emission standard	National II
Engine standard	Yuchai
Optional engines	Shangchai
Pattern	6 cylinder
Rated power (KW)	191.2
Rated speed (r/min)	2200
Clutch	15inch ; Dry ; Double disc
Gearbox	16+16/(Optional32+32)
Axle	TS
Tire	16.9-28/18.4-42
PTO speed (r/min)	760/850 850/1000
Hydraulic lifting system type	Strong pressure double cylinder
Balance weight	Front40KG×11/Rear60KG×4



# GLORY

## Tractor **GL3004**

Min operating weight  
**9840KG**

Rated power (KW)  
**221.0kw**

Rated speed(r/min)  
**2200r/min**

## GL3004 technical specifications

### GL3004-TS

GL3004-TS	
Model	GL3004
Dimensions with frame (mm)	5600×2780×3000
Dimensions with cab (mm)	5600×2780×3200
Wheelbase (mm)	2830
Min operating weight (kg)	9440(Without cab)/9840(With cab)
Min ground clearance (mm)	450
Emission standard	National III
Engine standard	Yuchai
Optional engines	Shangchai
Pattern	6 cylinder
Rated power (KW)	221.0
Rated speed (r/min)	2200
Clutch	15inch ; Dry ; Double disc
Gearbox	16+16/(Optional32+32)
Axle	TS
Tire	16.9-28/18.4-42
PTO speed (r/min)	760/850 850/1000
Hydraulic lifting system type	Strong pressure double cylinder
Balance weight	Front40KG×11/Rear60KG×4



**GLORY**



**Qingdao Ever Glory Machinery Co., Ltd**

Address: Huangdao District, Qingdao City, Shandong Province

TEL: +86-18153282521

Email: [market@everglormachinery.com](mailto:market@everglormachinery.com)

Website: [www.everglormachinery.com](http://www.everglormachinery.com)